

Revision Date 09-21-2019

Version 3

SECTION 1: IDENTIFICATION

Product identifier

Product Code(s) 42795500-M
Product Name HOCUT 795 B

Other means of identification

UN Number UN3082

Recommended use of the chemical and restrictions on use

Recommended Use Cutting fluid Metalworking fluid
Uses advised against Any other purpose.

Suppliers name, address and phone number

Manufacturer, Importer, Supplier

Houghton Australia Pty. Ltd.
287 Wickham Road
Moorabbin, Victoria
Australia, 3189
+61 1300 736 642

Emergency telephone number

For further information, please contact: ProductStewardship@houghtonintl.com

Emergency Telephone 3E Company (+)1 760 476 3960 (Code 333938)
Australia: (+)61 1 800 686 951
Australia (+)61 280 363 166
New Zealand: (+)64 800 451719

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2A - (H319)

Label elements

Exclamation mark



Signal word
WARNING

Hazard statements

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific treatment (see .? on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No	Weight-%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	25% - 50%
Neutralised Dicyclohexylamine	101-83-7*	2.5% - 10%
1-Aminopropan-2-ol	78-96-6	2.5% - 10%
2,2',2"-Nitrilotriethanol	102-71-6	2.5% - 10%
Neutralised 1-Aminopropan-2-ol	78-96-6*	2.5% - 10%
Glycerol	56-81-5	0% - 1%
Neutralised boric acid	10043-35-3*	0% - 1%
1,2-Benzisothiazol-3(2H)-one	2634-33-5	0% - 1%

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General advice

Do not get in eyes, on skin, or on clothing. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation

Remove to fresh air.

Skin contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.

Eye contact	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not rub affected area. Seek immediate medical attention/advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.
<u>Most important symptoms and effects, both acute and delayed</u>	
Symptoms	Redness. Rash. Itching. Eye damage/irritation.
<u>Indication of any immediate medical attention and special treatment needed</u>	
Note to physicians	Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Use CO2, dry chemical, or foam. Water spray or fog. Cool containers / tanks with water spray.

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke)

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

Special protective equipment and precautions for fire fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem emergency action code •3Z.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Recommended Shelf Life

Shelf life 12 months

Incompatible materials

None known based on information supplied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	
2,2',2''-Nitrilotriethanol	TWA: 5 mg/m ³ (+)	TWA: 5 mg/m ³	
Glycerol	TWA: 10 mg/m ³ containing no asbestos and <1% crystalline silica inhalable dust, mist	TWA: 10 mg/m ³ mist, inhalable dust containing no asbestos and <1% free silica	

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields.

Skin and body protection Wear protective gloves/clothing.

Hand protection Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Hygiene measures

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Thermal hazards

None under normal use conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
Information on basic physical and chemical properties

Physical state	liquid	Appearance	hazy amber
Odor	amine-like	Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH	9.6	@5%
Melting point / freezing point	Not Determined	
Boiling point / boiling range	> 100 °C / > 212 °F	
Flash point	Not Determined	
Evaporation rate	Not Determined	
Flammability (solid, gas)	Not Determined	
Flammability Limit in Air		
Upper flammability limit:	Not Determined	
Lower flammability limit:	Not Determined	
Vapor pressure	Not Determined	
Vapor density	Not Determined	
Relative density	0.970	g/cm3 @15.5°C
Solubility(ies)	Emulsifies	
Partition coefficient	Not Determined	
Autoignition temperature	Not Determined	
Decomposition temperature	Not Determined	
Kinematic viscosity	> 22 cSt @ 40 °C	
Explosive properties	Not applicable	
Oxidizing Properties	Not applicable	

Other Information

Viscosity, kinematic (100°C)	Not Determined	
Pour Point	Not Determined	
VOC Content (ASTM E-1868-10)	113 g/L	ASTM E 1868-10
VOC content	Not Determined	

SECTION 10: STABILITY AND REACTIVITY
Reactivity

None under normal use conditions.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION**Acute toxicity****Information on likely routes of exposure****Product Information - Principle Routes of Exposure**

Inhalation Based on available data, the classification criteria are not met.

Eye contact Causes eye irritation.

Skin contact Irritating to skin.

Ingestion Based on available data, the classification criteria are not met

Symptoms Moderate skin irritation. Corrosive - causes irreversible eye damage.

Numerical measures of toxicity - Product Information

ATEmix (oral) 5,626.00 mg/kg
ATEmix (dermal) 21,736.00 mg/kg
ATEmix (inhalation-dust/mist) 50.10 mg/l

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information

Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
1-Aminopropan-2-ol	2098 mg/kg (Rat)	1851 mg/kg (Rabbit)	
2,2',2''-Nitrilotriethanol		> 16 mL/kg (Rat) > 2000 mg/kg (Rabbit)	
Neutralised 1-Aminopropan-2-ol	2098 mg/kg (Rat)	1851 mg/kg (Rabbit)	
Glycerol	12600 mg/kg (Rat)	> 21900 mg/kg (Rat)	
Neutralised boric acid	3500 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 0.16 mg/L (Rat) 4 h
1,2-Benzisothiazol-3(2H)-one	1020 mg/kg (Rat)	4115 mg/kg (Rat)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye irritation Causes severe eye damage. Irritating to eyes.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Contains a known or suspected reproductive toxin. May impair fertility. May cause harm to the unborn child.
Specific target organ systemic toxicity (single exposure)	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Exposure levels	See section 8 for more information
Interactive effects	None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Neutralised Dicyclohexylamine		62: 96 h Brachydanio rerio mg/L LC50 static	
1-Aminopropan-2-ol	32.7: 72 h Scenedesmus subspicatus mg/L EC50	2520: 96 h Pimephales promelas mg/L LC50 210: 96 h Carassius auratus mg/L LC50 215 - 464: 96 h Leuciscus idus mg/L LC50	108.82: 48 h Daphnia magna mg/L EC50
2,2',2"-Nitrilotriethanol	216: 72 h Desmodemus subspicatus mg/L EC50 169: 96 h Desmodemus subspicatus mg/L EC50	10600-13000: 96 h Pimephales promelas mg/L LC50 flow-through 1000: 96 h Pimephales promelas mg/L LC50 static 450-1000: 96 h Lepomis macrochirus mg/L LC50 static	1386: 24 h Daphnia magna mg/L EC50
Neutralised 1-Aminopropan-2-ol	32.7: 72 h Scenedesmus subspicatus mg/L EC50	2520: 96 h Pimephales promelas mg/L LC50 210: 96 h Carassius auratus mg/L LC50 215 - 464: 96 h Leuciscus idus mg/L LC50	108.82: 48 h Daphnia magna mg/L EC50
Glycerol		54000: 96 h Oncorhynchus mykiss ml/L LC50	>10000: 24 h Daphnia Magna mg/L EC50
Neutralised boric acid	>28: 72 h Selenastrum capricornutum mg/L EC50	1020: 72 h Carassius auratus mg/L LC50 flow-through 627: 96 h Oncorhynchus tschawytscha mg/L LC50	115 - 153: 48 h Daphnia magna mg/L EC50
1,2-Benzisothiazol-3(2H)-one	0.11: 72 h Selenastrum capricornutum mg/L EC50 0.15: 72 h Desmodemus subspicatus mg/L EC50	2.18: 96 h Oncorhynchus mykiss mg/L LC50 5.9: 96 h Lepomis macrochirus mg/L LC50	2.94: 48 h Daphnia magna mg/L EC50

Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulative potential

Chemical name	Partition coefficient
Neutralised Dicyclohexylamine	3.5
1-Aminopropan-2-ol	-0.94
2,2',2"-Nitrilotriethanol	-2.53
Neutralised 1-Aminopropan-2-ol	-0.94
Glycerol	-1.76
Neutralised boric acid	-0.757
1,2-Benzisothiazol-3(2H)-one	0.4

Mobility

No information available

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS**Safe handling and disposal methods**

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Disposal of any contaminated packaging

Do not reuse empty containers.

Environmental regulations

No information available

SECTION 14: TRANSPORT INFORMATION**ADG**

UN Number	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)
Hazard Class	9
Packing Group	III
Environmental hazard	Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable
Special precautions for users	No information available
Hazchem emergency action code	*3Z
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE), 9, III

According to special provision AU01 - Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in; (a) packagings that do not incorporate a receptacle exceeding 500 kg(L); or (b) IBCs.

IMDG

UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)
Hazard Class	9

Packing Group	III
EmS-No	F-A, S-F
Vessel Stowage Location Code	A
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE), 9, III, Marine pollutant
IATA	
UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE)
Hazard Class	9
Packing Group	III
ERG Code	9L
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, 1,2-BENZISOTHIAZOL-3(2H)-ONE), 9, III

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 7

New Zealand

HSNO Hazard Classification:

6.3A - Substances that are irritating to the skin

6.4A - Substances that are irritating to the eye

HSNO Approval Number:

HSNO Approval Number: HSR002612

HSNO Group Standard: Metal Industry Products (Subsidiary hazard) GROUP STANDARD 2017.

International Inventories

Inventory information may be utilizing alternative CAS#s or exemptions beyond those stated within this document For further information, please contact: ProductStewardship@houghtonintl.com

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Does not Comply
KECL	Does not Comply
IECSC	Complies
ENCS	Complies
TCSI	Does not Comply
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
AICS - Australian Inventory of Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
ENCS - Japan Existing and New Chemical Substances
TCSI - Taiwan National Existing Chemical Inventory
NZIoC - New Zealand Inventory of Chemicals

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Chemicals Subject to Prior Informed Consent (PIC) Not applicable

Other Information

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Distillates (petroleum), straight-run middle	64741-44-2
Distillates (petroleum), heavy hydrocracked	64741-76-0
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5
Residual oils (petroleum), solvent deasphalted	64741-95-3
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4
Residual oils (petroleum), solvent-refined	64742-01-4
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8
Dec-1-ene, homopolymer, hydrogenated	68037-01-4
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

SECTION 16: OTHER INFORMATION

Revision Date

09-21-2019

Revision Note

This SDS has been revised in the following section(s), Company Logo.

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA	Time weighted average	STEL	Short term exposure limit
Ceiling	Maximum limit value:	(s) - Skin	Skin designation
+	Sensitizers	C	Carcinogen

STOT SE - Specific target organ systemic toxicity (Single exposure)
STOT RE - Specific target organ systemic toxicity (repeated exposure)
VOC - Volatile organic compounds

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet