

Revision Date 09-21-2019

Version 3

SECTION 1: IDENTIFICATION

Product identifier

Product Code(s) 42000401-M
Product Name HOCUT 400 K

Other means of identification

UN Number UN3082

Recommended use of the chemical and restrictions on use

Recommended Use Metalworking fluid
Uses advised against Any other purpose.

Suppliers name, address and phone number

Manufacturer, Importer, Supplier

Houghton Australia Pty. Ltd.
287 Wickham Road
Moorabbin, Victoria
Australia, 3189
+61 1300 736 642

Emergency telephone number

For further information, please contact: ProductStewardship@houghtonintl.com

Emergency Telephone 3E Company (+)1 760 476 3960 (Code 333938)
Australia: (+)61 1 800 686 951
Australia (+)61 280 363 166
New Zealand: (+)64 800 451719

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitization	Category 1 - (H317)

Label elements



Signal word
DANGER

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water
Take off contaminated clothing and wash before reuse
If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

May be harmful if swallowed
Toxic to aquatic life with long lasting effects

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	CAS No	Weight-%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	2.5% - 10%
1-Aminopropan-2-ol	78-96-6	2.5% - 10%
Neutralised Dicyclohexylamine	101-83-7*	2.5% - 10%
Sulfonic acids, petroleum, sodium salts	68608-26-4	2.5% - 10%
Amines, coco alkyl, ethoxylated	61791-14-8	2.5% - 10%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	1% - 2.5%
Neutralised 1-Aminopropan-2-ol	78-96-6*	1% - 2.5%
1,2-Benzisothiazol-3(2H)-one	2634-33-5	0% - 1%

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General advice

Do not get in eyes, on skin, or on clothing. May produce an allergic reaction. Immediate

	medical attention is required.
Inhalation	Remove to fresh air.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
Eye contact	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not rub affected area. Seek immediate medical attention/advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.
<u>Most important symptoms and effects, both acute and delayed</u>	
Symptoms	Redness. Rash. Itching. May cause allergic skin reaction. Eye damage/irritation.
<u>Indication of any immediate medical attention and special treatment needed</u>	
Note to physicians	Treat symptomatically. May cause sensitization of susceptible persons.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Extinguishing media which shall not be used for safety reasons

None

Specific hazards arising from the chemical

Hazardous decomposition products

None under normal use

Special protective equipment and precautions for fire fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem emergency action code •3Z.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place.

Recommended Shelf Life

Shelf life 12 months

Incompatible materials

None known based on information supplied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	Australia	New Zealand	New Zealand - Biological Exposure Indices (BEI)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	
Highly refined base oil (Viscosity >20.5 cSt @40°C)		TWA: 5 mg/m ³ STEL: 10 mg/m ³	

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tightly fitting safety goggles. If splashes are likely to occur, wear:.. Face-shield.

Skin and body protection Wear protective gloves/clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Hygiene measures Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove

and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Thermal hazards None under normal use conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Appearance	hazy amber
Odor	amine-like	Odor threshold	Not Determined

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH	9.5	@5%
Melting point / freezing point	Not Determined	
Boiling point / boiling range	Not Determined	
Flash point	Not Determined	
Evaporation rate	Not Determined	
Flammability (solid, gas)	Not Determined	
Flammability Limit in Air		
Upper flammability limit:	Not Determined	
Lower flammability limit:	Not Determined	
Vapor pressure	Not Determined	
Vapor density	Not Determined	
Relative density	0.99	g/cm3 @15.5°C
Solubility(ies)	emulsifiable	
Partition coefficient	Not Determined	
Autoignition temperature	Not Determined	
Decomposition temperature	Not Determined	
Kinematic viscosity	> 30 cSt @ 40 °C	ASTM D 445
Explosive properties	Not applicable	
Oxidizing Properties	Not applicable	

Other Information

Viscosity, kinematic (100°C)	Not Determined		
Pour Point	Not Determined		
VOC Content (ASTM E-1868-10)	189 g/L		ASTM E1868-10
VOC content	Not Determined		

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None under normal use conditions.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

None known based on information supplied.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information - Principle Routes of Exposure

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	May result in permanent damage including blindness.
Skin contact	Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Based on available data, the classification criteria are not met

Symptoms Moderate skin irritation. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Corrosive - causes irreversible eye damage.

Numerical measures of toxicity - Product Information

ATEmix (oral)	4,353.00 mg/kg
ATEmix (dermal)	13,737.00 mg/kg
ATEmix (inhalation-dust/mist)	50.10 mg/l

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information

Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
1-Aminopropan-2-ol	2098 mg/kg (Rat)	1851 mg/kg (Rabbit)	
Sulfonic acids, petroleum, sodium salts	>5000 mg/kg (Rat)	>500 mg/kg (Rabbit)	
Amines, coco alkyl, ethoxylated	= 500 mg/kg (Rat)		
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Neutralised 1-Aminopropan-2-ol	2098 mg/kg (Rat)	1851 mg/kg (Rabbit)	
1,2-Benzisothiazol-3(2H)-one	1020 mg/kg (Rat)	4115 mg/kg (Rat)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Serious eye damage/eye irritation	Causes severe eye damage.

Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (single exposure)	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Exposure levels	See section 8 for more information
Interactive effects	None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Crustacea
1-Aminopropan-2-ol	32.7: 72 h Scenedesmus subspicatus mg/L EC50	2520: 96 h Pimephales promelas mg/L LC50 210: 96 h Carassius auratus mg/L LC50 215 - 464: 96 h Leuciscus idus mg/L LC50	108.82: 48 h Daphnia magna mg/L EC50
Neutralised Dicyclohexylamine		62: 96 h Brachydanio rerio mg/L LC50 static	
Sulfonic acids, petroleum, sodium salts		>1000: 96 h Pimephales promelas mg/L LC50	>1000: 48 h Daphnia magna mg/L EC50
Amines, coco alkyl, ethoxylated		4.3: 96 h Brachydanio rerio mg/L LC50 19.6: 96 h Lepomis macrochirus mg/L LC50	12.1: 48 h Daphnia magna mg/L EC50
Neutralised 1-Aminopropan-2-ol	32.7: 72 h Scenedesmus subspicatus mg/L EC50	2520: 96 h Pimephales promelas mg/L LC50 210: 96 h Carassius auratus mg/L LC50 215 - 464: 96 h Leuciscus idus mg/L LC50	108.82: 48 h Daphnia magna mg/L EC50
1,2-Benzisothiazol-3(2H)-one	0.11: 72 h Selenastrum capricornutum mg/L EC50 0.15: 72 h Desmodesmus subspicatus mg/L EC50	2.18: 96 h Oncorhynchus mykiss mg/L LC50 5.9: 96 h Lepomis macrochirus mg/L LC50	2.94: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available

Bioaccumulative potential

Chemical name	Partition coefficient
1-Aminopropan-2-ol	-0.94
Neutralised Dicyclohexylamine	3.5
Sulfonic acids, petroleum, sodium salts	18.05
Neutralised 1-Aminopropan-2-ol	-0.94
1,2-Benzisothiazol-3(2H)-one	0.4

Mobility

Will likely be mobile in the environment due to its water solubility Miscible with water

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Safe handling and disposal methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Disposal of any contaminated packaging

Do not reuse empty containers.

Environmental regulations

No information available

SECTION 14: TRANSPORT INFORMATION

ADG

UN Number	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED)
Hazard Class	9
Packing Group	III
Environmental hazard	Yes
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable
Special precautions for users	No information available
Hazchem emergency action code	•3Z
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED), 9, III

According to special provision AU01 - Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in; (a) packagings that do not incorporate a receptacle exceeding 500 kg(L); or (b) IBCs.

IMDG

UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED)
Hazard Class	9
Packing Group	III
EmS-No	F-A, S-F
Vessel Stowage Location Code	A
Marine pollutant	This product contains a chemical which, although not listed, meets the IMDG criteria for being a marine pollutant
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED), 9, III, Marine pollutant

IATA

UN/ID no	UN3082
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED)
Hazard Class	9
Packing Group	III
ERG Code	9L
Description	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (NEUTRALISED DICYCLOHEXYLAMINE, AMINES, COCO ALKYL, ETHOXYLATED), 9, III

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

New Zealand

HSNO Hazard Classification:

- 6.1E - Substances that are acutely toxic
- 6.3A - Substances that are irritating to the skin
- 6.5B - Substances that are contact sensitisers
- 8.3A - Substances that are corrosive to ocular tissue
- 9.1B - Substances that are ecotoxic in the aquatic environment

HSNO Approval Number:

HSNO Approval Number: HSR002606

HSNO Group Standard: Lubricants (Subsidiary hazard) GROUP STANDARD 2017.

International Inventories

Inventory information may be utilizing alternative CAS#s or exemptions beyond those stated within this document For further information, please contact: ProductStewardship@houghtonintl.com

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Does not Comply
KECL	Does not Comply
IECSC	Complies
ENCS	Does not Comply
TCSI	Does not Comply
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
ENCS - Japan Existing and New Chemical Substances
TCSI - Taiwan National Existing Chemical Inventory
NZIoC - New Zealand Inventory of Chemicals

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Chemicals Subject to Prior Informed Consent (PIC) Not applicable

Other Information

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5
Residual oils (petroleum), solvent deasphalted	64741-95-3
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Distillates (petroleum), straight-run middle	64741-44-2
Distillates (petroleum), heavy hydrocracked	64741-76-0
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5
Residual oils (petroleum), solvent deasphalted	64741-95-3
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4
Residual oils (petroleum), solvent-refined	64742-01-4
Distillates (petroleum), hydrotreated middle	64742-46-7

Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8
Dec-1-ene, homopolymer, hydrogenated	68037-01-4
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

SECTION 16: OTHER INFORMATION

Revision Date 09-21-2019
Revision Note This SDS has been revised in the following section(s), Company Logo.

Key or legend to abbreviations and acronyms used in the safety data sheet

TWA	Time weighted average	STEL	Short term exposure limit
Ceiling	Maximum limit value:	(s) - Skin	Skin designation
+	Sensitizers	C	Carcinogen

STOT SE - Specific target organ systemic toxicity (Single exposure)
STOT RE - Specific target organ systemic toxicity (repeated exposure)
VOC - Volatile organic compounds

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet