

Defoamer MW

Metal Working Coolant Defoamer

DESCRIPTION

Defoamer MW is a uniquely different defoamer with wide latitude in applications. It has shown outstanding efficiency as a defoamer for coolants, effluents and industrial applications. Defoamer MW should be dispensed directly from the drum, without first forming an emulsion.

FEATURES

HOW TO USE

The recommended usage concentration rate for Defoamer MW is generally in the order of 10 to 20 ml per 100 litres (0.01% - 0.02%) of the coolant emulsion. This may be customised to suit individual needs or solutions, which may vary from time to time. Houghton strongly advises that you contact your Sales Representative to discuss before commencement of use.

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **PRODUCT** is a minimum of Twelve (12) months, unless otherwise specified.

PRODUCT is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

TYPICAL VALUES

Appearance	Tan, Opaque Liquid
Density @ 15°C	0.88
Type	Non-ionic
Flash point	>150°C
Brookfield Viscosity,	

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



HOUGHTON™

Houghton Australia Pty Ltd
 287 Wickham Road
 Moorabbin VIC 3189 Australia

Phone: +61 1300 736 642
 Fax: +61 1300 736 234
 Sales.au@houghtonintl.com
 www.houghtonintl.com