MACHINE TOOL CLEANER-AU FAST SOLVENT DETERGENT ACTION CLEANER

DESCRIPTION

FEATURES

MACHINE TOOL CLEANER-AU is a powerful, effective cleaner for machine tools and central coolant systems. Mix it with water for use. This makes a quick acting solvent-detergent solution that removes grease and gummy deposits from machine surfaces. It also purges caked residue and scum from coolant sumps, lines and fittings. Use it to clean return trenches and main reservoirs in central coolant systems

- Water based non flammable
- Cleans grease dirt from machine surfaces
- Ideal cleaner central coolant systems

Cleans scum from machine sumps

TYPICAL VALUES

Appearance Clear amber liquid

pH 2% 9.8

Flash Point °C Not applicable

Density 15°C 1.00

SHELFLIFE & AVAILABILITY

Under normal conditions the recommended shelf life for **MACHINE TOOL CLEANER-AU** is a minimum of Twelve (12) months, unless otherwise specified.

MACHINE TOOL CLEANER-AU is available in 205 litre drums. Other sizes may be available upon request, please contact your Houghton sales representative.

HOW TO USE

Five simple steps to clean your machine -

Dump old fluid from system. Add enough fresh water for thorough circulation.

Add 3 – 6 litres **MACHINE TOOL CLEANER-AU** per 100 litres of water in sump. Quantity required depends on condition of equipment.

Circulate solution for one to two hours, or until all deposits are loosened.

Make sure that all surfaces to be cleaned are reached by the solution. For caked deposits use high pressure flow to loosen. Residual deposits may trap live bacteria that will re-infect the system so clean thoroughly.

Drain – flush with fresh water.

Add fresh coolant to the machine system.

For optimum effectiveness – add 0.5-1 litre **MACHINE TOOL CLEANER-AU** per 100 litres to the system 24 hours before the final cleaning above.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

01 JUNE 2015 Version 1.0



Houghton Australia Pty Ltd 287 Wickham Road Moorabbin VIC 3189 Australia Phone: +61 1300 736 642 Fax: +61 1300 736 234 Sales.au@houghtonintl.com www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.